



Interpret / Compile UDFs and Their Usage

Advanced UDF
Modeling Course

© 2006 ANSYS, Inc. All rights reserved.

ANSYS, Inc. Proprietary

Advanced FLUENT Training
UDF Mar 2007

Fluent User Services Center
www.fluentusers.com



How to use the UDF

- ◆ First, we need to write and save the C-source file containing the appropriate **DEFINE_MACRO** routine(s).
- ◆ To use this file, the steps are:
 - 1: Interpret / Compile the UDF
 - 2: Start the solver (FLUENT) and read in your case/data files
 - 3: Assign the UDFs in the BC and/or other panels for the appropriate zones
 - 4: Set the UDF update frequency in the Iterate panel
 - 5: Run the calculation as usual
- ◆ **Note:** Values obtained from and returned to the solver by UDFs must be in SI units

© 2006 ANSYS, Inc. All rights reserved.

3-2

ANSYS, Inc. Proprietary

Interpreted Vs. Compiled Code

- ◆ UDFs can be 'interpreted' on-the-fly using the standard 'GUI'
 - does not need a separate compiler and are architecture-independent
 - It translates the C-source to assembly language
 - Executes the code on line-by-line instantaneously
 - performs slower than compiled UDFs
 - The interpreter resides in the computer's memory
 - involves extra memory usage
- ◆ UDFs can be precompiled before invoking in FLUENT
 - Needs a compiler
 - It translates the C-source to machine language (object modules)
 - Needs to follow a standard multi-step procedure (will be discussed later)
 - Creates 'shared libraries' linked with the rest of the solver

ALL INTERPRETED UDF-S CAN ALSO BE COMPILED
THOUGH THE CONVERSE IS NOT TRUE


Interpreted UDFs

- ◆ Interpreter limitations:
 - mixed mode arithmetic,
 - structure references etc.
 - cannot be linked to compiled system or user libraries
 - less powerful than compiled UDFs due to limitations in the C language supported by the interpreter
- ◆ In particular, interpreted UDFs cannot contain:
 - non ANSI-C prototypes for syntax
 - declarations of local structures, unions, pointers to functions, and arrays of functions
 - direct structure references
- ◆ Interpreted UDFs can indirectly access data stored in a FLUENT structure only via a set of macro-s

Interpreting the UDF

(2)

- ◆ Define → User Defined Functions → Interpreted...




- ◆ Click Interpret
- ◆ The assembly language code will scroll past window

Listing appearing on Fluent windows:


```
w_profile:
    .local.pointer thread (r0)
    .local.int position (r1)
0    .local.end
0    save
    .local.int f (r6)
8    push.int 0
10   save
    .local.int.
    .:
    .: } Skipping display here
.L1:
132  restore
133  restore
134  ret.v
```

Compiled UDF Directory Structure

Unix Tree




Windows Tree




UDF Compilation in F6.2

- ◆ To compile UDFs from within Fluent, use:
 - Define→User_Defined→Functions→Compile...
- ◆ Placing source routines in your working directory would be sufficient and necessary
- ◆ This GUI creates the directory structure below your working directory where you have your case and data files
- ◆ This GUI identifies the architecture as well as the version of fluent running and compiles only for the appropriate UDF version (2d/2ddp/3d/3ddp/or any parallel version)



UDF Compilation in F6.2


- ◆ Define→User_Defined Functions→Compile...
- ◆ Click on the “Add” button to browse and add source and header files
- ◆ Click on “Build” button to compile and then “Load” to load the library to a case file
- ◆ The compilation log appears on the Fluent console window and in a file named log
- ◆ To unload a compiled UDF, use Define→User_Defined Functions→Manage, select the library, then click Unload button



Using UDFs - Example

- ♦ A non-uniform inlet velocity is to be imposed on the 2D turbine vane shown below. The x-velocity variation is to be specified as

$$u(y) = 20 [1 - (y/0.067)^2]$$



A Source Code Example


```
#include "udf.h"

DEFINE_PROFILE(velocity_profile, thread, position)
{
    real x[3]; /* this will hold the position vector*/
    real y;
    face_t f;

    begin_f_loop(f, thread)
    {
        F_CENTROID(x,f,thread);
        y = x[1];
        F_PROFILE(f, thread, position) = 20.*(1.- y*y /
                                                (.067*.067));
    }
    end_f_loop(f, thread)
}
```


Activating the UDF

- ◆ Access the **boundary condition** panel
- ◆ Switch from **constant** to the **UDF** function in the **Velocity Magnitude** dropdown list



Run the Calculation

- ◆ Run the calculation as usual
- ◆ You can change the **UDF Profile Update Interval** in the **Iterate panel** (here it is set to 1)



Solution of Example problem

- ◆ The figure at right shows velocity field throughout turbine blade passage
- ◆ The bottom figure shows the velocity plot at the inlet
- ◆ Notice the imposed parabolic profile

